

UHD Commercial TV with Essential Smart Function

Commercial TV | UT640S Series (Colombia)

The UT640S Series is specifically designed for diverse business environments. By providing compatibility with AV Control systems and DPM (Display Power Management) as well as its smart connectivity, simple user friendly interface, and UHD picture quality, the UT640S series enhances ease of use while facilitating communications between businesses and their target audiences.



Simple Content Management



Higher Visibility



Better Usability



* All images in this datasheet are for illustrative purposes only.



SuperSign CMS

SuperSign CMS is Integrated management program supporting creation and management of digital media and content deployment, optimized for LG webOS signage. With its simple and intuitive menus and layout options, it enhances efficiency for content creation and editing, scheduling and distribution, so that it improves user experience. In addition, it supports multiple displays and accounts, is able to be linked to external databases, and allows server access from mobile devices.



Multiple Admins

Available Displays

SuperSign Control

SuperSign Control is the basic control software, and it can manage up to 100 displays through a single account and server. Power, volume, and scheduling can be remotely adjusted, and firmware updates supported.




Displays

Digital Signage

Embedded Content & Group Management

The embedded Content and Group Management System allows you to edit and play content, schedule playlists and groups, and control Signage via remote control, mouse and mobile phone without the use of separate PC or software. This makes content management much easier and more user-friendly.



* This images are provided for illustrative purposes, and the actual GUI may differ.
* All displays must be connected to the same network.

USB Cloning

USB Cloning increases efficiency in managing multiple displays for optimal operation since users don't have to set up each display one by one. Once users copy data to a USB device in one display, it can be easily distributed to the other displays through a USB plug-in.




Real-Time Remote Monitoring

Malfunctions or errors can be easily handled through real-time remote care. When an error occurs, notifications can be sent through the SNMP (Simple Network Management Protocol) protocol.

WOL(Wake-on-LAN)

WOL (Wake-on-LAN) enables users to turn on displays by sending the relevant packet through a network.



Perfect Picture Quality and Color

Enjoy Full HD content in 4K ULTRA HD quality, optimized by the 4K Upscaler. The 4K upscaler automatically upgrades Full HD content to ULTRA HD through several upscaling processes so that images look crisp and clear in any viewing situation. This LG TV can also express intense highlights, vivid colors, and deep black hues on the screen through HDR10.



Compatibility with AV Control Systems


The UT640S series has been certified Crestron Connected®, proving that it has a higher level of compatibility with professional AV controls. This results in seamless integration and automated control*, boosting business management efficiency.



* It is a network based control system.
Available AV control systems may differ by regions.






DPM (Display Power Management)

Display Power Management (DPM) can be configured to be On only when there is a TV signal present to manage power more efficiently.





DIMENSION (unit: mm)

Commercial TV | UT640S Series





* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.
 * UT640S series basically have a two-pole stand, but it is able to detach the stand from the body, per service environment (can be used as a wall-mount unit).

75"



65" | 55" | 49" | 43"



* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.

SPECIFICATION

Commercial TV | UT640S Series

UT640S series (Colombia)		75UT640S	65UT640S	55UT640S	49UT640S	43UT640S
DESIGN	Stand Type	2 Pole(No-Stand available)	2 Pole(No-Stand available)	2 Pole(No-Stand available)	2 Pole(No-Stand available)	2 Pole(No-Stand available)
	Front Color	Dark Meteor Titan	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black
DISPLAY	Inch	75	65	55	49	43
	Resolution	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)
	Brightness (cd/m ²)	350	400	400	400	300
BROADCASTING SYSTEM	TV Reception	DVB-T2	DVB-T2	DVB-T2	DVB-T2	DVB-T2
VIDEO	HDR (10 Pro / HLG)	•/•	•/•	•/•	•/•	•/•
AUDIO	Audio Output	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W
	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch
	DOLBY ATMOS	-	-	-	-	-
	One Touch Sound Tuning	-	-	-	-	-
	LG Sound Sync	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required
SUPERSIGN SW COMPABILITY	Content Management Software (SuperSign CMS), Control and Monitoring Software (Control/Control+), Simple Editor					
SIGNAGE FEATURE	Crestron Connected® (Network Based Control), DPM (Digital Power management), Time scheduler, RTC (Real Time Clock), NTP sync timer, BEACON, Embedded CM (Contents manager), Embedded GM (Group manager)					
SMART FEATURE	webOS 4.5, Smart Home (Launcher Bar), Web Browser, Pre-loaded App (YouTube only), Soft AP, Wi-Fi (802.11ac, Built-in type), Screen Share (Miracast), LG TV Plus App Compatibility, DIAL, Bluetooth Audio Playback, LG Sound Sync/bluetooth, Mobile Connection Overlay					
HOSPITALITY FEATURE	Hotel Mode(Installer Menu), Lock mode (Limited), Welcome Screen (Splash Image), Insert Image, IP Channel Manager, External Speaker Out (Int / Ext Variable/Fixed, 3.5mm, Stereo, Single ended Type(GND,L+,R+), 2W with 8Ω), RJP (remote jack pack) Compatibility (LG/Teledapt (RS232C), Teledapt/Guestlink (HDMI CEC)), Moving Picture Playback (SD/HD/Plus HD), Auto Off / Sleep Timer, Smart Energy Saving, Motion Eye Care					
MAINTENANCE FEATURE	USB Cloning, WOL, SNMP Diagnostics (Self Diagnostics (USB)), SI Compatible (TVLink Tuner), Simplink(HDMI-CEC, 1.4), IR Out (RS-232C, HDMI), Multi IR Code					
JACK INTERFACE	Set Side	HDMI In 2 (2.0), USB (2.0)				
	Set Rear	HDMI In (HDCP, 2.0), RF In, Digital Audio Out (Optical), RS-232C(D-Sub 9pin, Control & Service), RJ45 (Usage Purpose : Ethernet), External Speaker Out(3.5mm phone jack)2 (Spk-out 1, 4W (Stereo, R: 2.0W, L: 2.0W, 8Ω) Vol. Control 1), Debug (Phone Jack Type, Ext. SPK Volume Control Share)				
DIMENSION (UNIT : mm / kg)	VESA	600 x 400	300 x 300	300 x 300	300 x 300	200 x 200
	W x H x D / Weight (with stand)	1,693 x 1,048 x 345 / 35.4	1,463 x 914 x 269 / 21.6	1,244 x 786 x 231 / 14.5	1,110 x 709 x 231 / 11.3	973 x 623 x 216 / 8.1
	W x H(+) x D / Weight (without stand)	1,693 x 978 x 88.8 / 34.6	1,463 x 850 x 87.8 / 21.3	1,244 x 726 x 87.1 / 14.3	1,110 x 650 x 81.1 / 11.1	973 x 572 x 85 / 8.0
	W x H x D / Weight (Shipping)	1,839 x 1,116 x 231 / 45.7	1,600 x 970 x 190 / 28.4	1,360 x 835 x 175 / 19.5	1,193 x 770 x 158 / 13.4	1,060 x 660 x 152 / 10.2
POWER (UNIT : WATTS)	Voltage, Hz	100~240V, 50/60Hz	100~240V, 50/60Hz	100~240V, 50/60Hz	100~240V, 50/60Hz	100~240V, 50/60Hz
	Power Consumption(Typ.)	221W	181.8W	145W	104W	99.1W
	Stand-by	0.5W	0.5W	0.5W	0.5W	0.5W

* Specifications are subject to change without notice, so please contact LG sales team to verify before ordering.

Download
LG C-Display+
Mobile App
Google Play Store

www.lg.com/b2b
www.youtube.com/c/LGCommercialDisplay
www.facebook.com/LGInformationDisplay
www.linkedin.com/company/LGInformationDisplay

LG may make changes to specifications and product descriptions without notice.
 Copyright © 2020 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
 The names of products and brands mentioned here may be the trademarks of their respective owners.

